



C600 T125 - INDUSTRIAL THREE PHASE



STEELWORKS AND FOUNDRIES



SHIPYARDS



PAPER INDUSTRY



METALWORKING



- ✓ Complete steel construction
- ✓ Three powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Modularity is guaranteed to fulfil the client's needs
- ✓ Very suitable for the suction of large quantities of material
- ✓ Complete, quick and safe discharge



SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	12,5
Max waterlift	mmH2O	4000
Max air flow	m ³ /h	1100
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	75



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	30000
Material - Efficiency	IEC 60335-2-69	Polyester - L
Air load on filter	m ³ /m ² /h	367
Cleaning system		Manual



COLLECTION UNIT

Discharge system		Frontal discharge
Capacity	lt.	600



VOLUME

Dimensions	cm	220x100x220h
Weight	kg	270



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



FILTER UNIT

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The sucked material sets down into the container equipped with castors. Thanks to the safe and complete frontal discharge it's easy to empty the container without get in contact with dirt. The industrial vacuum is mounted on a robust epoxy painted chassis, with polyurethane castors and forklift intakes.



OPTIONALS

✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST